


CAST ACRYLIC

Type casting organic glass plate is made of methyl methacrylate (MMA) as raw material. In the process of plate production is with the method of pouring shape, then final cooling. Single body within a specific mould for bulk polymerization and organic glass plate. Can be made without color and colored transparent, translucent or opaque PMMA plate.



PRODUCT RANGE

| | |
|------------------|--|
| Length | 1520mm, 1850mm, 2440mm, 2450mm, 2550mm, 3050mm, and others |
| Width | 1020mm, 1220mm, 1250mm, 1550mm, 2050mm, and others |
| Thickness | 1mm-400mm |
| Density | 1.2g/cm ³ |
| Finished | Smooth, frosted, embossing, mirror or customized products |
| Available colors | All colors are available |

PMMA PERFORMANCE

General Features



- *Non-toxicity
- *Free coloring, bright color
- *Tough, hard and high gloss
- *Excellent shock resistance
- *Easy to clean and maintain
- *Can be molded and reprocessed
- *Mechanical processing and hot forming
- *Widely usage, easy to dyeing and painting
- *High degree of transparency, bright as crystal
- *Excellent weatherability, reputation of queen "plastic"
- *Good chemical resistance, superior to most other plastic materials.
- *Good electrical insulation, widely used for different electrical equipment.

FACTORY SHOW



PVC RIGID TRANSPARENT CLEAR SHEET



PRODUCT RANGE

◆ Extrude:

1. Thickness: 0.21-6.5mm
2. Width: <=1280mm
3. Category: pvc transparent sheet, pvc transparent sheet with both PE film masking
4. Color: natural transparent, transparent with blue tint
5. No Waves, Super clear, No fish eyes

◆ Canlender:

1. Thickness: 0.03-1.2mm
2. Width: <=1500mm
3. Category: pvc transparent sheet, pvc transparent sheet with both PE film masking
4. Color: natural transparent, transparent with blue tint
5. Super clear, Less waves, Less fish eyes

◆ Specifications:


- 1) Strong & rigid and suitable for chemical engineering
- 2) UV-protected, Anti-chemical corrosion
- 3) Sound insulation, sound absorption, heat insulation and heat preservation
- 4) Fire retardant and it can automatically extinguish by itself
- 5) Non-deformation, aging-resistant, color fastness

PACKAGE



PVC RIGID BOARD

PVC Celuka Foam board is a lightweight, expanded rigid PVC foam sheet that is used for a variety of applications including signs and displays, exhibit booths, photo mounting, interior design, thermoforming, prototypes, model making, and much, much more. It can be easily sawed, stamped, punched, die cut, sanded, drilled, screwed, nailed, or riveted. It can be bonded using PVC adhesives. Its properties include excellent impact resistance, very low water absorption and high corrosion resistance.



PRODUCT RANGE

| | | | |
|------------------|--|---------------------------|---------------------------|
| Length | 2440mm, 3050mm, 3600mm, 4800mm, 5490mm, length can be customized | | |
| Width | 1220mm, | 1560mm | 2050mm |
| Thickness | 3-40 mm, | 5-18mm | 5-18mm |
| Density | 0.33-0.9g/cm ³ , | 0.52-0.9g/cm ³ | 0.52-0.9g/cm ³ |
| Finished | Smooth, Mat and texture | Smooth | Smooth |
| Available colors | White, Black, Grey, Red, Yellow, Blue, Green | White | White |

TOLERANCES


| Range (based on thickness) | Thickness | Length | RWidth | Rectangularity |
|----------------------------|---------------|-------------|-------------|----------------|
| ≤12 | WITHIN ±0.2MM | WITHIN +5MM | WITHIN +3MM | WITHIN +5MM |
| >12 | WITHIN ±0.5MM | | | |

APPLICATION

Advertising Signs, billboards, displays, exhibition stands



PVC MATT SHEET




PRODUCT RANGE

- 1.Thickness: 0.05-3.0mm
- 2.Width: 1-1.5m
- 3.Normal Size: 900x1200, 915x1220mm
- 4.Density: 1.4-1.42g/cm³,
- 5.Colour: white black blue yellow and soon

◆ Specifications:

It is an exquisite lines on surface, clear matte material. Be fit for printing to make calendar, brand and etc. Also through thermoforming and other processing, to pack food and gift. In addition, through cutting, packing and other processing to make PVC matte binding cover. We also can do follow client's requirement to produce diversified fluorescence clear color, to make the product more beauty.

PACKAGE



PVC RIGID FILM FOR MEDICAL PACKING

Our pvc medical sheet is made by refining and calendaring hygienic pvc resin under SFDA's applicable regulations & national standards.

It is no poison, smell and pollution. Less rhyolite and crystal points, easy to forming.

Highly transparent, no impurity, and erosion insulating. Good light transmission, Strong impact resistance.



SPECIFICATION

| | | |
|-----------------------|--------------------------------|-----------|
| Size by roll | Width | 50-1500mm |
| Thickness by sheet | | 0.2-0.8mm |
| Density | | 1.36 |
| Color | transparent,white,amber,orange | |
| NAME OF INDEX | UNIT | INDEX |
| TENSILE-STRENGTH | MPA | >52 |
| IMPACT-STRENGTH | KJ/M2 | >5 |
| DROP IMPACT STRENGTH | NO FRACTURE | |
| VICAT SOFTENING PIONT | °C | 75 |
| DECORATION PLATE | | >75 |
| INDUSTRIAL PLATE | | >80 |



Characteristic:

- *Lead free
- *Bright-colored
- *Surface-glossy
- *High-transparent
- *Corrosion resistance
- *Good printing quality
- *Good chemical stability
- *Low temperature-tolerance
- *Less rhyolite and crystal points
- *Plays well in area of fire-prevention
- *Environmentally friendly, no smell and non-toxic



PVC CO-EXTRUDED FOAM BOARD

PVC Co-extruded Foam board is a lightweight, expanded rigid PVC foam sheet that is used for a variety of applications including signs and displays, exhibit booths, photo mounting, interior design, thermoforming, prototypes, model making, and much, much more. Comparing with PVC Celuka Foam sheet, PVC Co-extruded have more smoother and shiny surface, surface hardness is much better than Celuka, which will benfit for using in some application need very very hard and shiny surface. such as table top, interior decoration for boat & ship, vehicle, train.



What is the different between PVC Celuka and PVC Coextruded? Which kind should I choose?

- 1. Hardness & Stiffness:** Under the same thickness and thickness, the hardness of co-extruded is better than Celuka
- 2. Nail Holding Strength:** Under the same condition is Almost the same
- 3. Surface:** Co-extruded is more shiny and glossy than Celuka
- 4. Price:** Depend on the formulation

Conclusion: If you are looking for the material resistance of scratch and with more shiny surface, PVC Co-extruded will be your best choice.

PRODUCT RANGE

| | |
|------------------|--|
| Length | 2440mm, 3050mm, 3600mm, 4800mm, 5490mm, length can be customized |
| Width | 1220mm, |
| Thickness | 3-25mm, |
| Density | 0.45-0.9g/cm3, |
| Finished | Smooth and shiny |
| Available colors | White and colors |

TOLERANCES

| Range (based on thickness) | Thickness | Length | RWidth | Rectangularity |
|----------------------------|---------------|-------------|-------------|----------------|
| ≤ 12 | WITHIN ±0.2MM | WITHIN +5MM | WITHIN +3MM | WITHIN +5MM |
| > 12 | WITHIN ±0.5MM | | | |

TOLERANCES

For signs and displays, exhibit booths, photo mounting



Interior scale board for Yacht & Cruise ship ,vehicle, train



OFFSET PRINTABLE PVC CARD MATERIAL



SPECIFICATION

| Item NO. | Product Name | Thickness (mm) | Color | Vicat point | Surface Tention | Rougness | Width (mm) |
|------------|--|----------------|-------------|-------------|-----------------|-------------------|------------|
| 1 PVC-A | contacting IC card | 0.25-0.85 | White | 80±2℃ | ≥36 | Both sides matt | ≤1530 |
| 2 PVC-AB | Middle layer for credit card | 0.25-0.85 | White | 74±2℃ | ≥36 | Both sides matt | ≤1530 |
| 3 PVC-ABS | SIM card | 0.25-0.85 | White | 90±2℃ | ≥36 | Both sides matt | ≤1530 |
| 4 PVC-AC | Opaque card | 0.06-0.25 | White | 80±2℃ | ≥37 | Both sides matt | ≤1530 |
| 5 PVC-AD | Normal card | 0.10-0.85 | White | 80±2℃ | ≥34 | Both sides matt | ≤1530 |
| 6 PVC-ADE | Middle layer for nonfluorescence card | 0.10-0.85 | White | 80±2℃ | ≥34 | Both sides matt | ≤1530 |
| 7 PVC-AF-1 | Inlayer for contactless card | 0.06-0.60 | White | 72±2℃ | ≥37 | Both sides matt | ≤1530 |
| 8 PVC-AF-2 | Printed layer for contactless card | 0.06-0.25 | White | 78±2℃ | ≥37 | Both sides matt | ≤1530 |
| 9 PVC-PK | Poker | 0.10-0.85 | White | 78±2℃ | ≥36 | Glossy in surface | ≤1530 |
| 10 PVC-EA | Transparent IC card | 0.25-0.85 | Transparent | 78±2℃ | ≥36 | Glossy in surface | ≤1530 |
| 11 PVC-ABE | Middle layer for transparent credit card | 0.15-0.85 | Transparent | 74±2℃ | ≥37 | Both sides matt | ≤1530 |
| 12 PVC-ACE | Middle layer for transparent normal card | 0.15-0.85 | Transparent | 76±2℃ | ≥36 | Both sides matt | ≤1530 |
| 13 PVC-B | Overlay for credit card | 0.06-0.25 | Transparent | 72±2℃ | ≥35 | Both sides matt | ≤1530 |
| 14 PVC-E | Transparent printing sheet | 0.15-0.85 | Transparent | 76±2℃ | ≥35 | Both sides matt | ≤1530 |
| 15 PVC-ADL | Black printing sheet | 0.15-0.85 | Black | 80±2℃ | ≥35 | Both sides matt | ≤1530 |

APPLICATION



IC CARD

SIM CARD

MEMBER CARD

GIFT CARD

CREDIT CARD

PVC FREE FOAM

PVC Free foam sheet also call Closed-cell PVC foamboard is a lightweight rigid material used primarily in the manufacture of signs and displays. It is considered robust for outdoor use, being immune to rain and resistant to wind and sunlight. furniture, especially for the cabinet in kitchen & bathroom, advertising, traffic and transit, industry, etc.



PRODUCT RANGE

| | | | |
|------------------|--|----------------|----------------|
| Length | 2440mm, 3050mm, 3600mm, 4800mm, 5490mm, length can be customized | | |
| Width | 1220mm | 1560mm | 2050mm |
| Thickness | 1-25.4mm | 1-18mm | 1-10mm |
| Density | 0.33-0.9g/cm3, | 0.45-0.9g/cm3, | 0.45-0.9g/cm3, |
| Finished | Mat | | |
| Available colors | White, Black, Grey, Red, Yellow, Blue, Green | | |

TOLERANCES

| Range (based on thickness) | Thickness | Length | RWidth | Rectangularity |
|----------------------------|---------------|-------------|-------------|----------------|
| ≤12 | WITHIN ±0.2MM | WITHIN +5MM | WITHIN +3MM | WITHIN +5MM |
| >12 | WITHIN ±0.5MM | | | |

APPLICATION

Advertising Signs, billboards, displays, exhibition stands



PVC STATIONERY SHEET

CHARACTER

- 1.High chemical stability,fine anti-fire,super-transparent;
- 2.Highly UV.stabilized,good mechanical properties,high hardness and strength;
- 3.The sheet also has well ageing resistance,good selfextinguishing property and reliable insulativity;
- 4.Moreover the sheet is waterproof and has very good smoothsurface,and is non deformable;



PRODUCT RANGE



| | |
|----------------|---------------------------------------|
| Size(MM) | A3,A4 or any size required by clients |
| Thickness(MM) | 0.125-0.35 |
| Density(g/cm3) | 1.33-1.37 |
| Color | Transparent,yellow,red,blue,green |
| Surface | Glossy or Matt or Grain |
| Feature | Anti-sticky,waterproof,non-deformable |
| Application | For stationery |

APPLICATION

Used for stationery packing such as notebook cover,saddlebag inner leaf and so on.



PVC SOFT GLASS/MULTIPLE EXTRUSION SOFT FILM

Thickness:0.6-3.0mm

Width:<1800mm

Length:10-30m/Roll

| specification | thickness | width | softness (PHR) | Weight/roll | standard | remark |
|--------------------------------|---|---|----------------|-------------|----------|--------------|
| Normal clear | 0.05MM-0.5MM | Less than 2m | 26-65 P | 20-60kgs | any | Calender |
| Super clear | 0.1MM-0.5MM | Less than 1.8m | 30-65P | 20-60kgs | any | Calender |
| Soft sheet,curtain,table cloth | 0.5MM-5.0MM | Less than 1.22m | 38-70P | 10-40kgs | any | Cast machine |
| Pvc color film | The same as normal clear,super clear,soft sheet,curtain,table cloth | | | | | Color any |
| Pvc color super clear film | The same as normal clear,super clear,soft sheet,curtain,table cloth | | | | | Color any |
| Pvc embossed film | The same as normal clear,super clear,soft sheet,curtain,table cloth | | | | | Need samples |
| Pvc carpet protective sheet | 0.6MM-0.8MM | one side is nail lines,another side is wave lines | | | any | |
| Special pvc film | Be according to clients demand to make | | | | | |



◆Features:

- a.Easy to clean
- b.Non-toxic, tasteless, green products.
- c.Adapt to the joint of all kinds of plane and crooked surface.
- d.Adapt to the process of all kind of suction.
- e.Product have the performance of heat resistant and wear-able.
- f.Able to produce smooth surface, printing surface, grain surface, frosted surface and so many kinds.



◆use:

- a.Mainly used in the table cloth of table.
- b.Instead of glass windows
- c.Curtain of super-market, factory or restaurants.
- d.To protect your furniture.

PVC RIGID FILM FOR DRUM COVER



PRODUCT RANGE



APPLICATION



(14) Films for adhesive tape

Thickness: 0.08-0.2mm

◆The features:

- a. Insulation, nice electric property
- b. We can produce and design the emboss tools according to clients' requirements
- c. Flaming resistant.
- d. Adopt low lead and cadmium formula, according with Rohs instruction request.

◆use:

Be suitable to various electrician adhesive tape, warning adhesive tape and protective tape after sizing treatment.



(16) Films for floor

Thickness: 0.07-1.00mm

◆The features:

- a. Wear resistant. We can produce all kinds of emboss according to customer's request

◆use:

Be used in home, airport, hospital and office



(15) Films for urine bag

Thickness: 0.09-0.3mm

◆The features:

- a. Good physics function
- b. We can provide all kinds of emboss according to clients' requirements
- c. Suitable to be printed, we can provide all sorts of specifications as well
- d. Low toxicity, we use the formula which contains low lead and cadmium

◆use:

Be suitable to the treatment



(17) Wallpaper

Thickness: 0.07-0.30mm

◆The features:

- a. Good level of flatness and film's surface is exquisite
- b. Various types
- c. Contraction rate is nice

◆use:

The wallpaper is suitable to the high level hotel and top guesthouse



(2) Films for the stationary

Thickness: 0.07-0.5mm

◆The features:

- a. The contraction rate is low when be heated, suitable for high-frequency processing
- b. Dull polish embossed films have the elegant lines and good transparency.
- c. Semi-rigid films have the nice vacuum molding compatibility

◆use:

- a. The transparent films, dull polish embossed films can be used in cold-laminating, albums, ID box etc.
- b. The solid colored, embossed, printing processing, pearl luster and adhesive films may do for the slipcase, the title page uses.
- c. Semi-rigid films are suitable for the vacuum using.



(3) The films used for raincoat

Thickness: 0.15-0.5mm

◆The features:

- a. The elasticity is nice, feel soft and non-sticky
- b. Good tolerance to different climate, anti-aging
- c. Various of the products and can develop according to customers' requests.

◆use:

Can be used for the raincoat and the umbrella



(4) Films for wallpaper

Thickness: 0.07-0.3mm

◆The features:

- a. Good level of flatness, high performance of printing, suitable to be printed by all kinds of printing machines
- b. Films' surface is exquisite
- c. Contraction rate is nice.
- d. The films are low toxicity, and can be reached in flame-retardant as well

◆use:

The wallpaper, which has the functions of water proofing, killing insects and flame-retardant, are suitable to the high level hotel and top grade guest-house use after sticking with the cloth



(5) Films for curtain

Thickness: 0.09-0.26mm

◆The features:

- a. Flame resistant and sulfur tolerance
- b. Elegant colour and various types

◆use:

The curtain use.



(6) Films for the bath curtain

Thickness: 0.05-0.25mm

◆The features:

- a. Water proofing and good tolerance to all different climate
- b. Can 8 printing plate print and the patterns leading the trend, can develop the patent coordinate with the customer, beautiful patterns and full ranges.
- c. Good colour effect if the curtains are made from pearlite films



(8) Films for the clothes covering

Thickness: 0.07-0.15mm

◆The features:

- a. Suitable for high frequency processing
- b. Feel refreshing and easy to process

◆use:

TFilms are made into clothing sets, blankets sets bed sets, shoe sets, cushion kits and mechanical packaging jackets



(7) Films for the baby pants

Thickness: 0.05-0.15mm

◆The features:

- a. Feel refreshing;
- b. Feel soft and the tactility is nice, baby will feel comfortable for wearing it, do not hurt tender skin of the baby.
- c. The low level of the lead and cadmium, and no smell, do not hurt health of baby.
- d. Good performance of soapy water-resistant
- e. Varieties of printing patterns for the raincoat and the umbrella



(9) The films for the shopping bags

Thickness: 0.10-0.4mm

◆The features:

- a. The surface of the films always shining as the mirror
- b. The lightness is good for the pearlite films and pearlite adhesive films
- c. All kinds of printing films have the graceful patterns and good intensity

◆use:

Used in all sizes of the leather bags and shopping bags



(10) Films for the clothespress

Thickness: 0.19-0.3mm

◆The features:

- a. The colour of the printing is pastel, the pattern is novel.
- b. Update the printing patterns everytime.

◆use:

Used in plastic clothespress



(11) Normal transparent films/ normal clear films


Thickness: 0.045-0.7mm

◆The features:

- a. To spray some powders on the surface to make the films feel more refreshing and easy to process;
- b. The products can be accord with the low toxicity requirements of European standards EN71, the restrictions of the European 2005/84/EC about the six items of phthalate esters and the low poisonous power of ASTM-F-963, and so on.

◆use:

Can be processed by the high-frequency and needle vehicle machines, suitable to be used into licensing documents, the packing bags of the home textile, gifts and so on.



(12) Super transparent films/ super clear films

Thickness: 0.08-0.5mm

◆The features:

- a. Can produce colored and colorless super transparent films with high grade transparency and good glossing
- b. The products meet the international standards of the low toxicity, design meet customer's requirements
- c. The range of the hardness from 26PHR-60PHR (according to the samples)

◆use:

Fit for printing, high-frequency, car-processing, used for the package of high-grade goods



(13) Printing films

Thickness: 0.06-0.3mm

◆The features:

- a. Print various designed and colourful varieties in PVC film
- b. Bright-coloured, attractive looks, broad using.

◆use:

Being used for all sorts of tablecloth, bath curtain, charging toy, being decorating using and so on.



PVC FLEXIBLE FILM SERIES



PVC ROLLING FILM

PVC films are widely used in the daily life, which are the most important raw materials to make charging toys, shower curtainers, raincoats, stationary and so on.



(1) Films for the charging toys and the water-bed

Thickness: 0.17-1.0mm

The features:

- a. Complete ranges of the specifications, all kinds of finished products.
- b. Elegant and bright-colour printing, 8 printing plate print, pile coating
- c. Low levels of heavy metals (in order to meet some special requirements, the content of lead and cadmium is less than 20ppm, barium is less than 500 ppm, Cr is less than 100ppm)
- d. The remnants of solvent is low.
- e. The products can be accord with the requirements of the USA ASTM-F963, the Japanese toy safety standard (ST) and the European Union EN-71.
- f. Be able to meet the requirements of the European 2005/84/EC about the six items of phthalate esters, multiring hydrocarbon and nonyl phenol.



USE



Suitable for high-frequency processing, the product can be made into inflatable toys, floating row, inflatable boats, water beds, etc

QinYe LAMINATING FILM



The thickness of the laminating films is from 0.6mm to 3.5mm.
 With this kind of thickness, we can do the films in colour transparent, non-coloured super transparent.
 The laminating films have high transparency, nice gloss and strong adhesion after laminating.
 Products can meet the international low toxicity standard, the EN-71, the limit requirement of the 6 items of phthalate concerned about 2005/82/EC, ASTM-F-963 and so on.
 The laminating films are most used for soft glass, shoe materials, curtain, hand-bags and package of high grade goods.



CHRISTMAS PVC FILM

QinYe PRODUCT RANGE

1. Thickness: 0.05-0.5mm
2. Width: 50-1400mm
3. Length: 100m, 200m, 300m etc.
4. Density: 1.38-1.40g/cm³
5. Colour: dark green, light green, yellow and so on.
6. Feature: durability, stability, moisture resistance, frost resistance, low toxicity, cold-resistant etc. 3mm high quality clear pvc curtain flexible pvc film 50kg/roll, 1ton/pallet. PE film or brown paper film in side, wooden pallet



QinYe APPLICATION

For Christmas tree, Christmas tree leaves.



QinYe SPECIFICATIONS

Separated rigid PVC film, convenient to produce artificial Christmas tree leaves.
 The width, thickness and emboss of the film can be according to the customer's requirement.
 We devote to supply our customers goods with high quality and reasonable price.

QinYe USAGE AND PACKAGE



PVC RIGID BOARD



PRODUCT RANGE

- 1.Thickness:1-40mm
- 2.Width:1-1.5m
- 3.Normal Size:1000x2000mm 1300x2000mm 1220x2440mm.
- 4.Density:1.5g/cm³
- 5.Colour:Grey black white



APPLICATION


1. Advertising: sign board, display, pop-up display, exhibition board, screen printing, digital printing, computer lettering and marking boards.
2. Building: partitions, wallboard, indoor or outdoor decoration, ceiling, commercial decorating shelves, dustless room board.
3. Other: Molding boards, seashore dampproof equipment, art design materials, credit card, phone card, stationery, refrigeratory board, environmental protection plate.

Welding

Engineering

Printing

Building



SPECIFICATIONS

Good surface brightness ,no crack, Impact-resistant;
 Excellen strength and toughness performance;
 Non absorbent, Flame retarded;
 Weather resistant,water proof, acid proof, Resistant to chemicals and corrosion, Abrasive-resistant ,
 Excellent UV resistance;
 Standardized size , No deformation, resuable, Good insulation;
 Moisture resistance, Aging-resistant.

PVC RIGID FILM FOR LAMPSHADE

Our lampshade film was be widely used for light,
 Tab lampshade,wall mount lampshades,ceiling lampshades and so on.



For laminating with Fabric or do silk-screen
 printing/offset printing.
 Perfect decoration for lighting.
 UV stabilized film,antistatic treated,No stripes in
 the film
 The material is waterproof,oil-resistance,anti-
 corrosion,acid-proof and nontoxic.



SPECIFICATION

| Size by roll | | |
|-----------------------|--|-------------|
| WIDTH | ≤1500mm | |
| THICKNESS BY SHEET | 0.3-0.5mm | |
| DENSITY | 1.42 | |
| COLOR | White,clear,creamy white,creamy yellow | |
| NAME OF INDEX | unit | Index |
| TENSILE-STRENGTH | mpa | >52 |
| IMPACT-STRENGTH | kJ/m2 | >5 |
| DROP IMPACT STRENGTH | | no fracture |
| VICAT SOFTENING PIONT | °C | 75 |
| DECORATION PLATE | >75 | |
| INDUSTRIAL PLATE | >80 | |



PRODUCTS CHARACTER

- 1.High chemical stability,fine anti-fire,super-transparent
- 2.Highly UV.stabilized,good mechanical properties,high hardness and strength
- 3.The sheetaslo has wellagingresistance,good selfextinguishingproperty and reliable in sulativity
- 4.Moreover the sheet is waterproof and has very good smooth surface,and is non deformable
- 5.Application:chemical industry,oil industry,galanization,water purification equipments
- 6.Application:environment protection equipmets,medical appliance and soon
- 7.Importanitem:the sheet anti-stastic,anti-UV,anti-sticky